

## FORESLOPE PROTECTION

① SPACE TOP ROW OF STAPLES AT 18" CENTERS, BOTTOM ROW CENTERS. AT 36" CENTERS AND ALL OTHERS STAPLES AT

BE FILLED WITH SOIL

AND COMPACTED

 $\odot$ ② WHERE EROSIVE GULLIES HAVE DEVELOPED IN BACKSLOPE THEY SHALL PRIOR TO PLACEMENT OF MAT. IF EROSIVE RILL HAS DEVELOPED ADJACENT TO SHOULDER MATERIAL IT SHALL BE FILLED WITH SUITABLE SOIL AND COMPACTED PRIOR TO PLACE OF MAT.

## GENERAL NOTES:

- EXCELSIOR MAT FOR BACKSLOPE PROTECTION IS INSTALLED WITH STRIPS PLACED APPROXIMATELY PERPENDICULAR TO ROADWAY. LOCATIONS FOR SLOPE PROTECTION SHALL BE AS SHOWN ON DRAWINGS. EXCELSIOR MAT FOR FORESLOPE PROTECTION IS INSTALLED WITH STRIPS PLACED APPROXIMATELY PARALLEL TO ROADWAY. THE LOCATION, WIDTH AND NUMBER OF STRIPS SHALL BE AS SPECIFIED ON PROJECT PLANS.

FILE NO.: 1300-030	CEDAR RAPIDS METROPOLITAN AREA	
APPROVAL DATE: AUG 1999	STANDARD DETAILS FOR PUBLIC IMPROVEMENTS	
REVISION NO.:	SINTENTION DETAILS	5
REVISION DATE:		200
	(WOOD EXCELSION MAI) SHEEL I OF 2	1300-03

30

REVISION DATE:

ALLTRANS, INC.

City of Holy Cross Subdivision

1 No.3

Legend, Standard Details, And Bench Mark

SHEET NO. B.03 of

1300-030 <u>N</u>

Information

Dubuque County, Iowa

WOOD

**EXCELSIOR** 

SLOPE

PROTE

CTION DETAILS

Cedar Rapids, Iowa 52402 Phone: (319) 393-8726

PROJECT

ö

DRAWN BY: BGA APPROVED BY: GMH DATE: 10/10/2012

